




- Brass Manifold
- Solid Ceramic Plungers
- Stainless Steel Plunger Guides and Check Valves
- Bronze Connecting Rods
- Heavy Duty Flat Base High Pressure Seals
- 57.6 oz. Capacity Vented Oil Bath Crank Case
- Max Fluid Temp, 160°F

NKD Series Direct Drive, Hydraulic Flange Plunger Pumps

NKD Series super duty plunger pumps include a wide range of models with flow rates from 14.9 to 26.4 GPM and pressures up to 4350 PSI.

Other drive options include 30mm solid shaft or gas engine gear reduction

Applications include general pressure cleaning,, construction, hydro-excavation UHP fire fighting, mining and street cleaning.


	Model	Flow		Pressure		Plunger Dia.	Crankshaft		Power	Seal Kit	Valve Kit	Wt.
		GPM	l/min	PSI	bar		Stroke	Code				
1750 RPM	NKD 15.0/44 R MI	14.9	56.6	4350	300	22mm	30.0mm	F	43.5 EBHP	6061.10	6061.J1	67 lbs
	NKD 24.0/25 R MI	23.8	90.2	2465	170	28mm	30.0mm	F	39.3 EBHP	6061.12	6061.M6	67 lbs
	NKD 27.0/25 R MI	26.4	100.0	2465	170	28mm	34.0mm	7	43.6 EBHP	6061.12	6061.M6	67 lbs

NOTE: All pump models available with left-hand drive option. Substitute 'L' for 'R' in model number when ordering (ex. NKD 15.0/44 L MI)



MAX FLOW
MAX PRESSURE
RATED PUMP SPEED
POWER REQUIREMENT
LUBRICATION

26.4 GPM / 100.0 L/MIN
2465 PSI / 170 BAR
1750 RPM
43.6 HP ELECTRIC
57.6 OZ UDOR LUBE



Revised 2-23-2022

Part #	Description	Qty
0002.79	CRANKSHAFT MI	1
0007.26	OIL SEAL D35	3
0007.59	OIL SEAL	1
0014.01	PLUNGER GUIDE	3
0023.31	UPPER RING D28 ^{D E}	3
0115.06	BUSHING D35	3
0208.26	OIL SIGHT GLASS	1
0208.B3	BACK COVER	1
0209.51	CRANKCASE	1
0248.08	BALL BEARING	2
0301.36	SLINGER RING ^A	3
0302.13	SPACER	3
0501.35	BEARING FLANGE	1
0517.18	BEARING FLANGE - MI	1
0602.51	GASKET - PUMP BODY	1
0605.43	GASKET - D17	1
0614.15	SET SCREW	3
0635.29	HIGH PRESSURE SEAL KIT D28 ^{B E}	3
1101.41	O-RING - VALVE ^{C E}	6
1101.60	O-RING - PLUNGER BOLT ^A	3
1101.A9	O-RING - PRESSURE RING ^{B D E}	3
1101.H6	O-RING - OIL SIGHT GLASS	1
1101.L3	O-RING - VALVE PLUG ^E	6
1101.Q1	O-RING - BEARING FLANGE	4
1205.03	CERAMIC PLUNGER D28	3
1208.46	PLATE	1
1221.15	PRESSURE RING D28 ^D	3
1240.R9	LIFTING HOOK M10	1
1401.05	RIVET 3.5X8	2
1401.06	RIVET D4X10	2
1403.14	WASHER - PLUNGER BOLT ^A	3
1403.57	WASHER M8	6
1411.02	SERRATED WASHER D8	6
1411.03	WASHER	12

Part #	Description	Qty
1412.20	BONDED WASHER D27.05 (G3/4")	1
1412.28	BONDED WASHER D42.9 (G1-1/4")	1
1502.22	PIN	3
1506.36	SNAP RING	2
1512.09	PIN D5X20	6
1534.07	GASKET - BEARING FLANGE	1
1534.08	SPACER / GASKET	1
1603.64	PLUG 3/8"	1
1603.74	PLUG G3/4"	1
1603.B8	OIL SIGHT GLASS W/GASKET	1
1603.D3	PLUG G1-1/4"	1
1603.G8	VALVE PLUG D28/30 ^E	6
1604.14	HEAD D28/30 ^E	1
1625.19	OIL CAP W/GASKET	1
1804.22	HEX BOLT M10X100	8
1805.02	ALLEN BOLT	8
1805.23	ALLEN BOLT M8X40	6
1805.62	ALLEN BOLT M6X20	12
1807.19	PLUNGER BOLT ^A	3
6002.L1	CRANKCASE ASSEMBLY	1
6006.A2	VALVE ASSEMBLY W/O O-RING ^{C E}	6
6017.R3	COMPLETE MANIFOLD ASSEMBLY NK D28	1
6020.02	CONNECTING ROD	3
6030.29	LOW PRESSURE SEAL KIT D28 ^{B E}	3
6180.01	CONNECTING ROD ASS'Y COMPLETE	3
6061.12	WATER SEAL KIT (KIT 12)	1
6061.19	BRASS RING KIT D28 (KIT 19)	1
6061.M6	VALVE KIT (KIT 182)	1
6061.Z8	PLUNGER BOLT KIT (KIT 254)	1

^A Parts in 6061.Z8 (Kit 254).

^B Parts in 6061.10 (Kit 10).



^C Parts in 6061.J1 (Kit 281).

^D Parts in 6072.19 (Kit 273).

^E Parts in 6017.R3 (Complete Manifold Assembly).

*Dimensional Drawings are
Shown in Millimeters.
To Convert to Inches,
Multiply Dimension x 0.03937*

NK SERIES PUMPS - MI Flange, 28/30mm Plungers



TORQUE SPECS

Ref.	Description	Ft./lb.	Nm	Loctite®
1	Head Bolts	37	50	-
2	Valve Caps	88	120	243
3	Inlet Cap	133	180	-
4	Outlet Cap	88	120	243
5	Bearing Flange Bolts	37	50	-
6	Rear Cover Bolts	8	11	-
7	Connecting Rod Bolts	19	25	243
8	Plunger Bolts	22	30	270
9	Valve Cover Bolts	-	-	-
10	Oil Drain Plug	8	11	-

