



VB 9

PA VB9 unloader valve

The PA VB9 by-pass valve can work with flow rates up to 30 l/min and with pressures up to 220 bar. The valve body is made of brass. The version with knob is fitted with locknut for minimum and maximum pressure regulation. The VB 9 is normally used with plunger pumps designed to work on professional high pressure washers or fixed installations for car-wash applications.

FIELDS OF APPLICATION



High
pressure
washer



Car-Wash

TECHNICAL DATA

Max pressure (bar)	220
Max flow rate (l/min)	30
Body	brass

EMILTEC Srl a socio unico

Sede Legale e Amministrativa: Via Carlo Boetti, 8/B • 42124 Reggio nell'Emilia • Italy

Tel +39.0522.941825 • Fax +39.0522.1601370 • C.F. e P.IVA 02674440355

www.emiltec.com info@emiltec.com



PART NUMBERS

PN	KNOB	INLET	OUTLET	BY-PASS	JIT DELIVERY
1160220000	NO	G 3/8" F	G 3/8" F	G 3/8" F	
1160225000	YES	G 3/8" F	G 3/8" F	G 3/8" F	
--	--	--	--	--	
1160222624	spare kit				

MORE INFORMATION

- Brand: PA
- G 1/4" pressure gauge port
- Available with integrated microswitch
- Made in Italy

EMILTEC Srl a socio unico

Sede Legale e Amministrativa: Via Carlo Boetti, 8/B • 42124 Reggio nell'Emilia • Italy

Tel +39.0522.941825 • Fax +39.0522.1601370 • C.F. e P.IVA 02674440355

www.emiltec.com info@emiltec.com

