



## DESCRIPTION

Conical or round head small size nozzles.

## MAIN FEATURES

Available with or without front jets, for use with high-pressure cleaners, compact channel-jets or secondary purge truck reels for cleaning and clearing domestic or industrial drains.

For greater breakthrough and penetration force (e.g. for removing grease blocks or ice), variants with different front jet configurations are available.

In cases where very small dimensions are required, nozzles with hose shanks connected directly to the 3/16" or 1/4" hose can be used.

## RECOMMENDATIONS

For effective and efficient operation, the nozzles must be specially configured (with regard to the size of individual holes), depending on the characteristics of the pump (flow rate and pressure) and the cross-section, length and type of high-pressure hose. This information must be provided by the customer at the time of order and must be compatible with the technical specifications of each individual nozzle. The operator must choose a working pressure compatible with the pipeline conditions: high working pressure values could cause structural damage to the pipe walls.

Maximum Pressure: 250 bar

## TECHNICAL SPECIFICATIONS

Part No.		∅ x L							
		mm	kg					lit/min	mm
Conical head									
<b>5500.07</b>	1/8"	15 x 15	0,008	Drilled	35°	-	-	20 - 60	20 - 60
<b>5500.07A</b>	1/8"	15 x 15	0,008	Drilled	35°	1 x drilled	0°	20 - 60	20 - 60
<b>5500.07F2</b>	1/8"	15 x 15	0,008	Drilled	35°	2 x drilled	0° / 30°	20 - 60	20 - 60
<b>5500.07TR</b>	1/8"	15 x 15	0,008	Drilled	35°	4 x drilled	0° / 30°	20 - 60	20 - 60
Round head									
<b>3518.00</b>	1/4"	18 x 29	0,025	Drilled	35°	1 x M4	0°	25 - 80	25 - 125
<b>3519.00</b>	3/8"	23 x 31	0,04	Drilled	35°	1 x M4	0°	30 - 90	30 - 90
<b>3519.00M</b>	3/8" M	21 x 37	0,05	Drilled	35°	1 x M4	0°	35 - 150	35 - 150
<b>3519.00</b>	3/8"	23 x 31	0,040	Drilled	35°	1 x M4	0°	30 - 90	50 - 150
<b>3519.00M</b>	3/8" M	21 x 37	0,050	Drilled	35°	1 x M4	0°	30 - 90	50 - 150