

SELF-PRIMING PUMPS

made in ITALY

ETM

X · PRO



Pressure regulating knob with anti-tampering device

Manopola regolazione pressione con dispositivo anti-manomissione



LW-K 250

PRO VERSIONS
Pump with 3 integral ceramic pistons. Oil sight glass. Brass pump heads

VERSIONI PRO
Pompa con 3 pistoni in ceramica integrale. Visore livello olio. Testate in ottone



GXR

X VERSIONS
Comet electrical pump with three axial pistons arranged vertically with pump at the bottom and an all-metal construction without any plastic used for the structural components

VERSIONI X
Elettropompa Comet a tre pistoni assiali disposta in verticale con pompa in basso e costruzione interamente in metallo, senza materiale plastico nei componenti strutturali



FOR MORE INFO:
MAGGIORI INFORMAZIONI:



GENERAL FEATURES · *CARATTERISTICHE GENERALI*

- Easy to transport thanks to a practical top grip and anti-vibration supports
- Induction 2-pole motor (2800 rpm) on ETM 150 X model
- 4-pole motor (1400 rpm) on ETM 150 PRO model
- Built-in professional unloader valve with ejector
- EASY START device
- Total Stop system
- Rotary switch
- Motor thermal protection

- *Semplicità di trasporto mediante confortevole impugnatura superiore ed appoggio su supporti antivibranti*
- *Motore a 2 poli a induzione (2800 giri/min) per modello ETM 150 X*
- *Motore a 4 poli (1400 giri/min) per modello ETM 150 PRO*
- *Valvola di regolazione professionale integrata con eiettore*
- *Dispositivo EASY START*
- *Dispositivo Total Stop*
- *Interruttore rotativo*
- *Protezione termica del motore*
- *Uso semiprofessionale gravoso (uso professionale per ETM 150 PRO)*

TECHNICAL FEATURES · *CARATTERISTICHE TECNICHE*

CODE *CODICE*	MODELS *MODELLI*	PUMP *POMPA*	Ph	V	Hz	MAX bar	MAX MPa	WORK bar	WORK MPa	WORK l/h	HP	kW	kW	kg	(L x W x H) cm
9055 0016	ETM 150 X	GXR	1	230	50	150	15	30 ÷ 135	3 ÷ 13,5	280 ÷ 600	3 ,0	2,2	2,9	25	26 x 47 x 37
9055 0011	ETM 150 PRO	LW-K 250	1	230	50	150	15	30 ÷ 135	3 ÷ 13,5	280 ÷ 600	3 ,0	2,2	2,9	35	26 x 47 x 37

STANDARD EQUIPMENT · *DOTAZIONE STANDARD*

X



GC 201 gun with protection
Pistola GC 201 con protezione

PRO



GC 251 gun with protection
Pistola GC 251 con protezione

X



Lance with adjustable jet, with nozzle
Lancia getto regolabile con ugello

PRO



Bent lance with detergent head, without nozzle
Lancia angolata con testina detergente, senza ugello

PRO



15° spray nozzle, 1/4" MEG connection
Ugello con getto a lama 15° attacco 1/4" MEG

X | PRO



R1 1/4" 10 m rubber delivery hose kit
Kit tubo mandata in gomma 10 m R1 1/4"