DAKOTA™ 429 SUB & SLURRY (PUMP OUT)

SPECIALTY
WET ONLY USE CASE

2400	2	180L/PM	90L	PLASTIC
WATTS	MOTORS	WATER FLOW	TANK CAPACITY	MATERIAL



HERO INNOVATIONS

ECO
75% Recycled eco-friendly plastic

STRONG
Aluminium encased plastic poles

GASKET
Exclusive fusion casted in base seal



NOTE: WASTE HOSE IS NOT SUPPLIED.

APPLICATIONS

- Pumping Out Large Volume of Water
- Wet Cleaning Only





STANDOUT FEATURES

- 2 x double stage motor with by-pass cooling.
- Professional submerged pump allows holding tank to be automatically emptied during operation via float
- Ultra shock proof plastic holding tank & UV and shock resistant plastic head.
- Independent motors with ON/OFF illuminated switches.
- Sound absorbent filter to ensure low noise levels.
- Powerhook™ 2-stage strong flexible nylon core cleat for easy remove of head.

STANDARD EQUIPMENT

2.5m Flexible hose with connection ø38mm	2 x plastic tubes ø38mm	Handle with air regulator ø38mm	Wet Floor tool ø38mm
			

TECHNICAL DATA 0:00

DAKOTA™ 429 SUB & SLURRY (PUMP OUT)

Product Code	10304/2/50
Intended Application	**Wet Only**
Cable Length	8.5m
Air Flow	420m³/h
Water Flow	180l/pm
Water-lift	2470mmH²O
Tank Capacity	90L
Material	Plastic (Polyethylene)
Diameter of Accessories	ø38mm
Standard Hose Length	2.5m
Sound Pressure Level	74dB

PUMP FEATURES

Pump Type	Plastic
Pump Power	370 watts
Pump Capacity	180l/pm
Delivery Head	7m

MOTOR FEATURES

Power / Voltage	**2400 Watts / 240v**
Motor(s) / Stage	2 / 2

DIMENSIONS & WEIGHT

Vacuum Dimensions / Weight	450mm(L) x 500mm(W) x 950mm(H) / 26KG

WARRANTY(S)

Vacuum	1 Year(s)

OPTIONAL CONSUMABLES

NYLON BAG (700 MICRON)	FTDP00559

OPTIONAL ACCESSORIES

ADDITIONAL Ø38MM FLEXIBLE HOSE	50200

The manufacturer reserves the right to modify design features and technical facts without notice; due to our principals of continuous improvement.
*Coverage against defects in material and workmanship (refer to Jetwave's and component partners T&Cs).

V2.2 08/21