HYNOX™ 170

PROFESSIONAL
DAILY USAGE

1650	11	ELECTRIC MOTOR 3HP 1 PHASE	1450RPM	HOT WATER
PSI	L/PM	MOTOR TYPE	DRIVE	OUTPUT



HERO INNOVATIONS

SSC™
Stainless Steel Cover & Chassis

DTS™
Delayed Total Stop Protection System

APPLICATIONS

- Food & Beverage Cleaning
- Wineries & Barrel Cleaning
- Agriculturist
- Vehicle Cleaning





STANDOUT FEATURES

Udor® Italian triplex plunger pump running at 1450RPM delivers more performance and longer life.

Maintenance free low speed, electric motor, air cooled.

Jetwave Safety System™ (JSS) thermal and safety valve to prevent overheating in excessive bypass and over pressurisation.

Brass adjustable unloader valve, for user flexibility.

Delayed Total Stop Protection System (TSS™) for operational longevitiy.

Vertical 90% fuel efficient environmentally friendly V3 diesel fired hot water burner system.

STANDARD EQUIPMENT



J5000™ High Pressure Gun + Twin Lance with Nozzles.



10m Double Wire Braid Hose with M22 Couplings.



TECHNICAL DATA 0:00

HYNOX™ 170

Product Code	10246C
Pressure / Flow Rate	**1650 PSI (110 BAR) / 11 L/PM**
Max Water Inlet / Outlet Temp	60°C / 90°C
Class (ASNZS: 4223)	A (1,210 Bar/Litres)
Usage Frequency	Professional: 4 Hours Daily
Nozzle Size	045
Frame Structure	**Stainless steel** chassis with stainless steel cover

MOTOR FEATURES

Motor / Power	Induction / 2.2kW / 1 Phase / 13.8AMP / 240v / 50Hz
Cable Length / Control	**5M** / Delayed Total Stop DTS™

HYDRAULIC FEATURES

Pump / Head / Pistons	**Udor® Italian** Triplex Plunger / Brass / Ceramic
Motor Pump Coupling / Pump RPM	**Direct / 1450RPM**
Unloader Valve	Independent - Adjustable
Safety Valve	Yes
Detergent Injector	Yes - Downstream low pressure

THERMAL FEATURES

Burner Model	Vertical V3
Fuel Supply / Capacity / Consumption	Diesel / 24L / 5.14 L/PH
Coil / Housing Material	Mild steel / Stainless Steel

DIMENSIONS & WEIGHT

Machine Dimensions / Weight	Trolley: 920mm(L) x 600mm(W) x 730mm(H) / 135KG (approx.)

WARRANTY(S)

Unit / Pump Warranty*	1 Year(s)
Motor Warranty*	1 Year(s)
Heating Coil Warranty*	2 Year(s)

OPTIONAL ACCESSORIES

30m Hose Reel (REQUIRES MOUNTING BRACKET)	1060CMPL
Hose Reel Mounting Bracket	90030HRP
Additional High Pressure Hose	52001
JW3 Foaming Lance w/1L Tank	JWA221
Turbo Head w/Lance (300BAR)	JWA160
15" Hammerhead - w/lance	JWA-FSC15-CMPL

The manufacturer reserves the right to modify design features and technical facts without notice; due to our principals of continuous improvement.
*Coverage against defects in material and workmanship (refer to Jetwave's and component partners T&Cs).

V2.3 04/22

JETWAVE GROUP
10-16 Smith Street, Thebarton, 5031, South Australia, AU +61 8 8371 3599 sales@jetwave.com.au jetwavegroup.com