TERREMAX®
LIQUID HANDLING PRODUCTS

NOW AVAILABLE AT BAR GROUP



SMARTER HANDLE
NO MORE SKINNED KNUCKLES

Introducing the TerreMax Smart Handle – the next level of convenience, control and innovation. Designed to make every interaction smarter and easier, it's a game-changer for your everyday needs!

MANIFOLD VALVES
WITH SMARTER HANDLE

MADE WITH Viton® A Brand of The Chemours Company

MADE IN USA



124 MV100CF

Pressure: 150 PSI
Ends: 1" Flange x 1" Flange
Port : 1"
Seals: Viton®



124 MV200CF

Pressure: 150 PSI
Ends: 2" Flange x 2" Flange
Port: 1 1/2"
Seals: Viton®



124 MV220CF

Pressure: 100 PSI
Ends: 2" FP Flange x 2" FP Flange
Port: 2"
Seals: Viton®



124 MVS220CF

Pressure: 100 PSI
Ends: 2" FP Flange x 2" FP Flange
Port: 2"
Seals: Viton®



124 MVS220FP

Pressure: 100 PSI
Ends: 2" FP Flange x 2" Female NPT
Port: 2"
Seals: Viton®



124 MVS300CFFP

Pressure: 100 PSI
Ends: 3" Flange x 3" Flange
Port: 3"
Seals: Viton®



124 MVSF220FP

Pressure: 100 PSI
Ends: 2" FP Flange x 2" M Adapter
Port : 2"
Seals: Viton®



124 MVSF300FP

Pressure: 100 PSI
Ends: 3" Flange x 3" M Adapter
Port: 3"
Seals: Viton®



124 VSF200CF

Pressure: 100 PSI
Ends: 2" Flange x 2" M Adapter
Port: 1 1/2"
Seals: Viton®

SCAN THE QR CODE FOR VIDEO

TO VIEW THE SMART HANDLE IN ACTION



MANIFOLD VALVES

Take your fluid management to the next level with TerreMax manifold valves! Engineered for strength, durability and dependable performance, TerreMax delivers reliable flow control with easy quarter-turn operation. Built with chemical-resistant materials and quality sealing components, these valves are designed to handle the demands of agricultural spraying and liquid transfer applications.

With versatile connection options and a practical, space-saving design, TerreMax manifold valves help simplify installation and maintenance, keeping your operation running smoothly when it matters most. Choose TerreMax for a smart, dependable solution you can count on!



124 MSU100E

Pressure: 125 PSI
Ends: 1" Flange x 1" Flange
Ball Opening : 1"
Seals: EPDM



124 MSUFT100E

Pressure: 125 PSI
Ends: 1" Flange x 1" F NPT
Ball Opening : 1"
Seals: EPDM

BAR

CONTACT BAR GROUP ON 02 4577 2144 OR VISIT WWW.BARGROUP.AU

TERREMAX®
LIQUID HANDLING PRODUCTS

NOW AVAILABLE AT BAR GROUP

CAMLOCK COUPLINGS

MADE IN USA



124 150C

Pressure: 125 PSI
Ends: 1-1/2" F Coupler x 1-1/2" Hose Barb
Series: C
Seals: EPDM



124 150E

Pressure: 125 PSI
Ends: 1-1/2" M Adapter x 1-1/2" Hose Barb
Series: E



124 150F

Pressure: 125 PSI
Ends: 1-1/2" M Adapter x 1-1/2" Male NPT
Series: F



124 200C

Pressure: 125 PSI
Ends: 2" F Coupler x 2" Hose Barb
Series: C
Seals: EPDM



124 200E

Pressure: 125 PSI
Ends: 2" M Adapter x 2" Hose Barb
Series: E



124 200F

Pressure: 125 PSI
Ends: 2" M Adapter x 2" Male NPT
Series: F

FLANGE CLAMPS

Designed to provide a secure, reliable connection for flange systems, flange clamps offer strength and durability in demanding applications. Built for dependable performance and ease of installation, TerreMax flange clamps help ensure a firm fit and long-lasting reliability across a range of industrial and piping applications.



124 FCP100

Size: 1"
Type: Hinge
Material: Plastic



124 FCP200

Size: 2"
Type: Hinge
Material: Plastic



124 FCP220

Size: 2" FP
Type: Hinge
Material: Plastic

MANIFOLD FITTINGS

Manifold flange fittings provide a secure, reliable connection between pumps, manifolds and fluid handling components. Designed for efficient flow and dependable sealing, they help simplify installation and maintenance while supporting reliable performance in demanding applications.

FLANGE



124 M100075BRB

Size: 1"
Ends: Flange x 3/4" Hose Barb



124 M200150BRB

Size: 2"
Ends: Flange x 1 - 1/2" Hose Barb

MANIFOLD STRAINER



124 MLST15080

Type: 2" Manifold T Strainer Clean Out Plug
Filter: 80 Mesh SS Screen
Seals: EPDM (Viton® available upon request)

BAR

CONTACT BAR GROUP ON 02 4577 2144 OR VISIT WWW.BARGROUP.AU