"HAND ROTARY PUMP"
Compact in Design & Light Weight

Applicable for low viscosity.



SB-25

■ Applications

- Heavy fuel oil A
- Diesel
- Kerosene

*Oil temperature is over 10°C



■ Specification

Model	SB-20	SB-25
Discharge Volume	20 L (5 USG) / 105 Rotations	20 L (5 USG) / 72 Rotations
Impeller Material	PPS	
Suction Pipe	1001 mm	1038 mm
Delivery Hose	ø20 × 1100	ø25 × 1280
Net Weight	3.8 kg (8.4 lbs) (1 unit)	5.8 kg (12.8 lbs) (1 unit)
Gross Weight	24 kg (52.9 lbs) (6 units)	25 kg (55.1 lbs) (4 units)
Dimensions L×W×H (mm)	1050 × 235 × 130	1080 × 200 × 210
Packing Unit	6	4

Light weight & Economical to Use

Made of strong plastics.

■ Applications

(PP-25)

- Dispensing small volumes of liquid
- Heavy fuel oil A
- Kerosene
- Diesel
- Water
- Wine

(PP-25C)

- Solvent



PP-25 PP-25C



PP-25 PP-25C

■ Specification

Model	PP-25	PP-25C
Discharge Volume	20 L/min (5 USG/min)	
Material	Polyethylene	
Pump Length	1190 mm	
Suction Pipe	878 mm	
Delivery Hose	ø25 × 1162 mm	
Net Weight	0.4 kg (0.9 lbs) (1 unit)	
Gross Weight	11 kg (24.2 lbs) (20 units)	
Dimensions L×W×H (mm)	1225 × 450 × 255	
Packing Unit	20	

■ PP-25C Chemical Compatibility Rating Information

Rating Scale	
○	No Effect
△	Moderate Effect
×	Not Recommended
N	Information Not Available

	Chemical (100% concentration unless noted)	Rating
A	Acetone	×
	Ammonium Hydroxide	N
C	Chlorine	○
D	Deionized Water	△
	Diesel Fuel	○
E	Ethanol	○
G	Gasoline	△
	Glycol	N
H	Hydrochloric Acid (20%)	○
	Hydrochloric Acid (37%)	○
	Hydrochloric Acid (100%)	○
I	Isopropyl Alcohol	N
K	Kerosene	○
L	Lacquer Thinner	×
M	Methanol	○
	Methyl Chloride	×
	Methyl Ethyl Ketone	×
	Mineral Spirits	N
	Motor Oil	○
N	Nitric Acid (20%)	△
	Nitric Acid (50%)	△
	Nitric Acid (Concentrated)	△
O	Oil, Hydraulic	○
P	Paint	×
	Phosphoric Acid (< 40%)	○
	Phosphoric Acid (≧40%)	○
S	Salt Water	○
	Seawater	○
	Sodium Hypochlorite	N
	Sodium Hydroxide (20%)	N
	Sodium Hydroxide (50%)	N
	Sodium Hydroxide (80%)	N
	Sulfuric Acid (<10%)	○
	Sulfuric Acid (10–75%)	○
	Sulfuric Acid (75–100%)	○
W	Water	○
X	Xylene	△