SC1500 3.0

18.040-xx-2



Advantages:

- New: Minimised leakage 10 l/min at 1000 bar and 13 l/min at 1500 Bar
- Less wear due to front protection
- High water jet density due to water brake and sapphire inserts
- Low flow due to 2 or 4 jets

Area of application:

- Surface cleaning & preparation
- Removes old paint, scale & corrosion
- Concrete scabbling

Specifications:

Product (2 or 4 Inserts)		min	max	ØxL
18.040-B-2	3/8“ BSPP	13 l/min / 3.4 gpm (2) 18 l/min / 4.8 gpm (4)	1500 bar / 22,000 psi	107x60 mm / 4.2x2.4“
18.040-NB-1	3/8“ NPT	10 l/min / 2.6 gpm (2) 13 l/min / 3.4 gpm (4)	1000 bar / 14,500 psi	107x60 mm / 4.2x2.4“
18.040-MB-2	M26 x 1.5	13 l/min / 3.4 gpm (2) 18 l/min / 4.8 gpm (4)	1500 bar / 22,000 psi	107x60 mm / 4.2x2.4“
18.040-C-2	1/2“ BSPP	13 l/min / 3.4 gpm (2) 18 l/min / 4.8 gpm (4)	1500 bar / 22,000 psi	107x60 mm / 4.2x2.4“
18.040-UBL-2	9/16“ UNF LH	13 l/min / 3.4 gpm (2) 18 l/min / 4.8 gpm (4)	1500 bar / 22,000 psi	107x60 mm / 4.2x2.4“